ENCLOSURE HEATER WITH FAN

CSF 032 | 03201.0-01



This is a compact PTC enclosure heater with fan and tamper-proof thermostat to prevent frost and condensation forming in casings and installation spaces. A plastic sheathing makes the heating safe to touch during application.

- Designs available with integrated tamper-proof thermostat (switch-on/off temperature: + 25 °C / + 15 °C or + 15 °C / + 5 °C)
- Compact, slim construction with high heating capacity
- Clip fixing for 35 mm DIN rail and screw fixing
- User safety: Touch-safe plastic casing

OVERVIEW TECHNICAL DATA


Device type	Fan heater; Integrated control; Touchsafe
Temperature monitoring	Overheating protection in the event of fan failure with automatic reset
Protection class	II
Protection type	IP20
Heating element	PTC resistor (PTC)
Casing	Plastic to UL94 V-0, black
AC/DC	AC
Operating voltage	220 V - 240 V
Inrush current	12 A
Frequency	50;60 Hz
Heating capacity	1000 W
Axial fan	63 m³/h
Service life	>50000 h
Switch-off temperature	25 °C
Switch-on temperature	15 °C
Surface temperature	< + 80 °C
Operating temperature	-40 °C - 60 °C
Operating humidity	≤90 % RH
Storage humidity	≤90 % RH
Storage temperature	-40 °C - 70 °C
Connection type	IEC power plug according to IEC320 C18
Connection	IEC power plug according to IEC320 C18
Mounting	Screw fixing
Installation position	Airflow direction "in" vertical / connection at the bottom
Height	88 mm

Width	66 mm
Depth	152,5 mm
Weight	500 g
Item number accessories 1	244379
Item number accessories 2	244380
Item number accessories 3	237009
Accessory 1	Supply line with IEC power plug to IEC320 C17, 1 m
Accessory 2	Supply line with IEC power plug to IEC320 C17, 2 m
Accessory 3	Safety bracket
Note	Tolerance ±5 K;Other switch-off and switch-on temperatures on request;The scope of delivery does not include female connectors and supply lines for the electrical connection. Supply lines can be ordered separately, see accessories;Heating capacity at +25 °C (+77 °F) ambient temperature; switch-on temperature tolerance +5K.

ACCESSORIES

Article number	Depth
237009	
244379	1000 mm
244380	2000 mm


TECHNICAL DRAWINGS




View: back side

Screw fixing

Clip fixing



Connection cable with female power insert connector according IEC320 C17



Heating capacity / Ambient temperature diagram
CS 032 / CSF 032

