# ELECTRICAL SOCKET

## SD 035 | 03505.0-00




Electrical socket for installation on 35 mm DIN rail. Quick, screwless electrical connection using pressure clamps. Designs with and without fuse are available.

- Versions with and without fuse
- Quick mounting
- Electrical connection with pressure clamps
- Large variety of country-specific versions

## OVERVIEW TECHNICAL DATA

| | |
|---|---|
| Device type | Sockets |
| Socket | IT |
| Protection class | I |
| Protection type | IP20 |
| Casing | Plastic to UL94 V-0, light grey |
| AC/DC | AC |
| Frequency | 50;60 Hz |
| Nominal current socket | 6 A |
| Operating temperature | -45 °C - 70 °C |
| Operating humidity | ≤90 % RH |
| Storage humidity | ≤90 % RH |
| Storage temperature | -45 °C - 70 °C |
| Connection | 3 x pressure clamps for stranded wire and rigid wire 0.5 - 2.5 mm² |
| Design | With fuse |
| Mounting | Clip for 35 mm DIN rail, EN 60715 |
| Height | 92 mm |
| Width | 62 mm |
| Depth | 48 mm |
| Weight | 200 g |
| Note | With fuse: Microfuse Ø 5 x 20 mm |

## TECHNICAL DRAWINGS

