# DRAINAGE DEVICE

## DD 084 | 08410.0-00





Drainage device for draining condensation from casings. In compliance with protection type IP66. No splash water penetrates as a water flow-through membrane drains the enclosure by capillary action.

- Protection type IP66
- Easy installation
- Weatherproof, splash water protection

## OVERVIEW TECHNICAL DATA

| | |
|---|---|
| Device type | Other accessories |
| Protection type | IP66/IP69K(EN40050-9) |
| Material sealing | NBR |
| Material hood | Plastic, umbra grey |
| Casing | Plastic, black |
| Operating temperature | -45 °C - 70 °C |
| Storage temperature | -45 °C - 70 °C |
| Cut-out dimensions | Ø50 +0,5 mm |
| Mounting | M50 x 1.5 |
| Height | Ø60 mm |
| Width | Ø60 mm |
| Depth | 37 mm |
| Installation depth | 21 mm |
| Weight | 60 g |
| Note | 200 ml/h with a water column of 5 mm; permissible wall thickness 0.5 - 5.5 mm<br>Installation instructions: The drainage element is installed in the base of the housing using the union nut in a hole of<br>Ø 50.5+0.5 mm is mounted. Ensure that the sealing gasket is located on the outer housing wall and that the<br>hole is burr-free. |

## TECHNICAL DRAWINGS

