FILTER FAN PLUS - SIZE 3 (176 X 176 MM)

FPO 018



Filter fan FPO size 3 (176 x 176 mm) for air conditioning enclosures and casings. Configuration: FPO - airflow direction "out" (design: intaking). Optimum filter fan for enclosures: The Filter Fan Plus draws the heating air from the enclosure to the outside. Cooler outside air enters the enclosure via the inlet filter. The air flow protects the electrical components.

- Filter fan with self-closing flaps as air outlet
- Only one filter mat required (on the inlet filter)
- Easy installation thanks to mounting frame with twist locks
- Effective air circulation
- Accessories: Hose-proof hood to increase the protection type to IP56

OVERVIEW TECHNICAL DATA

Device type	Filter fan Plus (DC)
Protection class	II
Protection type	IP54
Material hood	Plastic to UL94 V-0, light grey
Filter material	Plastic fibre with progressive structure
Filter mat	Flaps
Casing	Plastic to UL94 V-0, light grey
AC/DC	DC
Power consumption	12 W
Axial fan	Fan body aluminium, rotor metal
Average emission sound pressure level	63 dB(A)
Service life	>80000 h
Operating temperature	-25 °C - 70 °C
Operating humidity	≤90 % RH
Storage humidity	≤90 % RH
Storage temperature	-40 °C - 70 °C
Torque	0,8 Nm max.
Connection	3-pole clamp 2.5 mm²
Height	215 mm
Width	215 mm
Depth	142 mm
Installation depth	117 mm
Weight	1500 g
Mounting cut-out	176 x 176 mm
Item number accessories 1	08635.0-00

Item number accessories 2	11882.0-30
Item number accessories 3	08672.0-00
Accessory 1	Replacement filter mat FM 086
Accessory 2	Exit filter FP0 118 with filter mat G3
Accessory 3	Water jet protection hood FFH 086
Note	Drilling pattern for screw fixing marked on mounting frame.
Protection type UL	NEMA Type 12

PRODUCT VARIANTS

Article number	Operating voltage	Cooling airflow rate outlet filter	Cooling airflow rate blowing
01882.1-00	48 V	146 m³/h	277 m³/h
01882.2-00	24 V	141 m³/h	269 m³/h

FILTER MAT BAG

Article number	packaging_size	Filter mat	Mounting cut-out
08635.0-00	5 Piece	ISO coarse 55 % according to ISO 16890 (G3), grav. Initial gravimetric arrestance 57 %	168x168 mm

HOSE-PROOF HOOD

Article number	material_sealing	cutout_dimension	Height	Width	Depth	Weight
08672.0-00	Silicone, food safe	FPI/FPO 018 176 x 176 mm	359 mm	294 mm	68 mm	2000 g

INLET FILTER - SIZE 3 (176 X 176 MM)

Article number	Filter mat	Height	Width	Depth	Installation depth	Weight
11882.0-30	ISO coarse 55 % according to ISO 16890 (G3), grav. Initial gravimetric arrestance 57 %	215 mm	215 mm	50 mm	25 mm	400 g

TECHNICAL DRAWINGS