

Telescopic Lightning Protection Mast for Bucket or Concrete Foundations

TBM 22.35M FP565 STTZN (103022)





Dimension drawing

Type	TBM 22.35M FP565 STTZN
Part No.	**103022**
Material	**St/tZn**
Height above ground level (l1)	22380 mm
Mast segments	4
Max. gust wind speed with Concrete foundation	129 km/h
Max. gust wind speed with bucket foundation	129 km/h
Length of air-termination rod (l2)	5380 mm
Dimensions of flange plate	565 x 565 mm
Type of flange plate	8x Ø27 mm for 8x M24 (490 x 490 mm)
Dim. of on-site concrete foundation (l x w x h)	1800 x 1800 x 900 mm
Zinc coating acc. EN 1461	approx. 100 µm
Standard	EN 62561-(1+2)

Masterdata	
Net weight	1 pc(s)/st
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364129849
PU	1 st

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component