
RFS 16 10 1500 V2A (103 419)





Dimension drawing

Tubular air-termination rod with tapering (1000 mm), light design, chamfered, for protecting roof-mounted structures, chimneys etc., can be fixed in a concrete base (17 kg) with fixing wedge or by means of rod holders/ spacers.

Type	**RFS 16 10 1500 V2A**
Part No.	**103 419**
Total length (l1)	1500 mm
Reduced length	1000 mm
Material	StSt
Diameter Ø	16 / 10 mm
Wall thickness of tube (t1)	3 mm
Standard	EN 62561-2

Masterdata	
Net weight	1.1 kg/pc(s)
GTIN	4013364128651
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85389099

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

Special lengths of all air-termination rods / self-supporting air-termination rods are available upon request.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component