
# Datasheet: Air-Termination Rods D40

## FS D40 22 16 10 6500 KSV V2A (105 197)





Dimension drawing

| Type | FS D40 22 16 10 6500 KSV V2A |
|---|---|
| **Part No.** | **105 197** |
| Total length (l1) | 6500 mm |
| Length of tube (Ø40 x 5) | 4000 mm |
| Length of air-termination rod (Ø22 / 16 / 10) (l5) | 2500 mm |
| Max. free length with air-termination rod (l2) | 5000 mm |
| Clamping length (l3) | 1500 mm |
| Number of fixings | 3 |
| Max. gust wind speed | (Wall mounting with a free length of 5,000 mm) 190 km/h |
| Material of air-termination rod | StSt |
| Standard | EN 62561-(1+2) |

| Masterdata | |
|---|---|
| Net weight | 16.8 kg/pc(s) |
| GTIN | 4013364152113 |
| PU | 1 pc(s) |
| Customs tariff number (Comb. Nomenclature EU) | 85389099 |

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

Shorter transport lengths (separable pipe) are available upon request.
Special lengths of all air-termination rods / self-supporting air-termination rods are available upon request.