
Supporting tube for HVI Conductor, sub-roof installation

SR D50 1950 FS22 16 10 2500 DSH GFK AL (105281)





Dimension drawing

Supporting tube with internal sealing end and air-termination rod Ø22/16/10 mm.

Type	SR D50 1950 FS22 16 10 2500 DSH GFK AL
Part No.	**105281**
Material of air-termination rod	Al
Length of air-termination rod	2500 mm
Material of supporting tube	GRP / Al
Length of supporting tube	1955 mm
Transport length	2500 mm
Diameter Ø outside	50 mm
Length of insulating clearance	1560 mm
Wall thickness	4 mm
Material factor km	0.7
Permanent temperature range	-50 °C ... +100 °C
Type	UV-stabilised
Sleeve	60 x 5 mm
Max. gust wind speed	140 km/h
Pull-out force with a length of 500 mm	200 N (supporting tube insulator as per 62561-8)
Bending force with a length of 500 mm	200 N (supporting tube insulator as per 62561-8)
Standard	DIN EN IEC 62561-8 (VDE 0185-561-8)

Masterdata	
Net weight	4 kg/pc(s)
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364260962
PU	1 pc(s)

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component