
Supporting Tubes for HVI long Conductor

SR D50 3200 FS2500 IP SA HVI GFK AL (105326)





Dimension drawing

Supporting tube with internal sealing end and EB spring element.
Air-termination rod Ø22/16/10 mm.

Type	**SR D50 3200 FS2500 IP SA HVI GFK AL**
Part No.	**105326**
Material of air-termination rod	Al
Length of air-termination rod	2500 mm
Material of supporting tube	**GRP / Al**
Length of supporting tube	3200 mm
Transport length	3200 mm
Diameter Ø outside	50 mm
Length of insulating clearance	1535 mm
Wall thickness	4 mm
Material factor km	0.7
Permanent temperature range	-50 °C ... +100 °C
Type	UV-stabilised
Sleeve	60 x 5 mm
Pull-out force with a length of 500 mm	200 N (supporting tube insulator as per 62561-8)
Bending force with a length of 500 mm	200 N (supporting tube insulator as per 62561-8)
Standard	DIN EN IEC 62561-8 (VDE 0185-561-8)

Masterdata	
Net weight	0 g/pc(s)
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364157842
PU	1 pc(s)

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.