
# DEHNiso Combi Sets

## DICS WB D50 10 7200 GFK AL V2A (105470)





Dimension drawing

| Type | DICS WB D50 10 7200 GFK AL V2A |
|---|---|
| **Part No.** | **105470** |
| Total length | 7200 mm |
| Number of spacers | 3 |
| Number of fixing brackets | 3 |
| Length of supporting tube | 6200 mm |
| Max. gust wind speed | (Wall mounting max. free length 4,000 mm, Ø8 mm) 206 km/h |
| Material of supporting tube | **GRP / Al** |
| Type | two-piece |
| Length of air-termination rod | 1000 mm |
| Material of air-termination tip | **StSt** |
| Length of spacer | 1030 mm |
| Material of spacer | **GRP-Al-St/tZn** |
| Material factor km | 0.7 |
| Material of fixing bracket | **StSt** |
| Permanent temperature range | -50 °C ... +100 °C |
| Transport length | max. 3200 mm |
| Standard | DIN EN IEC 62561-8 (VDE 0185-561-8) |

| **Masterdata** | |
|---|---|
| Net weight | 14.65 kg/pc(s) |
| Customs tariff number (Comb. Nomenclature EU) | 85389099 |
| GTIN | 4013364100138 |
| PU | 1 pc(s) |

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component