
DEHNiso Spacers

DIDH 8 675 KT V2A GFK (106160)





Dimension drawing

Type	DIDH 8 675 KT V2A GFK
Part No.	**106160**
Conductor support Rd	8 mm
Material of conductor holder	StSt
Length (l1)	675 mm
Insulating clearance (l2)	590 mm
Application note	for elevated leading of the air termination conductor for increasing the separation distance, fixing in a concrete base for wedge mounting
Diameter Ø of spacer	16 mm
Colour of spacer	light grey (RAL 7035)
Conductor routing	loose
Rod/conductor holder	DEHNgrip
Material of spacer	**GRP**
Material factor km	0.7
Permanent temperature range	-50 °C ... +100 °C
Material of fixing bush	Al
Type	UV stabilised and weather resistant
Max. gust wind speed (base 8.5 kg, holder distance 1000 mm, Al Ø8 mm)	104 km/h
Max. gust wind speed (base 17 kg, holder distance 1000 mm, Al Ø8 mm)	176 km/h
Standard	DIN EN IEC 62561-8 (VDE 0185-561-8)

Masterdata	
Net weight	286.5 g/pc(s)
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364092938
PU	1 pc(s)

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

Verisons with other spacer bar lengths are available upon request.