
Spacers with conductor holder

DIDH 7.10 1015 V2A GFK16 (106175)





Dimension drawing

For fixing conductors at different supports, fixed conductor routing.

Type	DIDH 7.10 1015 V2A GFK16
Part No.	**106175**
Conductor support Rd	7-10 mm
Material of conductor holder	StSt
Length (l1)	1015 mm
Insulating clearance (l2)	935 mm
Material of bush	Al
Max. gust wind speed (holder distance 1000 mm, Al Ø8 mm)	140 km/h
Max. gust wind speed (base 17 kg, holder distance 1000 mm, Al Ø8 mm)	125 km/h
Standard	DIN EN IEC 62561-8 (VDE 0185-561-8)

Masterdata	
Net weight	447.8 g/pc(s)
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364100244
PU	1 pc(s)

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN (U.K.) LTD. • Unit 4 Velocity Point • Castleton Road • Armley • Leeds • LS12 2EE • United Kingdom • Tel. +44 113 541 8900 • info@dehn.co.uk • www.dehn.co.uk

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component