Air-Termination Rods GRP/Al

FS 16 10 2000 GFK AL (106210)



Dimension drawing

Type	FS 16 10 2000 GFK AL
Part No.	**106210**
Total length (l1)	2000 mm
Insulating clearance (l2)	975 mm
Material of air-termination rod / bush	Al
Material of spacer	GRP
Colour of spacer	light grey (RAL 7035)
Material factor km	0.7
Type	UV stabilised and weather resistant
Permanent temperature range	-50 °C ... +100 °C
Max. gust wind speed (1x base 17 kg, holder distance 1000 mm, Al Ø8 mm)	93 km/h
Max. gust wind speed (2x base 17 kg, holder distance 1000 mm, Al Ø8 mm)	105 km/h
Standard	DIN EN IEC 62561-8 (VDE 0185-561-8)

Masterdata	
Net weight	625 g/pc(s)
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364127630
PU	10 pc(s)

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component