
# Air-Termination Rods GRP/Al

## DIST 16 M10 1015 GFK (106220)






Dimension drawing

| | |
|---|---|
| **Type** | **DIST 16 M10 1015 GFK** |
| **Part No.** | **106220** |
| Total length (l1) | 1015 mm |
| Insulating clearance (l2) | 975 mm |
| Material of air-termination rod / bush | **Al** |
| Material of spacer | **GRP** |
| Colour of spacer | light grey (RAL 7035) |
| Material factor km | 0.7 |
| Type | UV stabilised and weather resistant |
| Permanent temperature range | -50 °C ... +100 °C |
| Standard | DIN EN IEC 62561-8 (VDE 0185-561-8) |

| **Masterdata** | |
|---|---|
| Net weight | 410 g/pc(s) |
| Customs tariff number (Comb. Nomenclature EU) | 85389099 |
| GTIN | 4013364128828 |
| PU | 10 pc(s) |

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component