
Roof conductor holder for roofs with clamping seam (e.g. RIB-ROOF Speed 500 from Zambelli)

DLH KF ZS 27 V2A (202861)





Dimension drawing

Roof conductor holder with slotted saddle clamp for fixing the HVI power Conductor onto metal roofs with clamping seam.

Type	DLH KF ZS 27 V2A
Part No.	**202861**
Material of roof conductor holder	StSt
Material of conductor holder	StSt
Material thickness	2.5 mm
Clamping range	approx. 18 / 22 mm
Conductor support Rd	27 mm
Conductor routing	fixed
Screw	M8 x 25, M6 x 16 mm
Standard	DIN EN IEC 62561-8 (VDE 0185-561-8)

Masterdata	
Net weight	217 g/pc(s)
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364354197
PU	25 pc(s)

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component