
Spacer bar with conductor holder

DILH 8 DS10 L280 K GR GFK (253315)





Dimension drawing

For insertion into the base plate (lock bush), stabilised with concrete block. For raised conductor routing, loose conductor routing.

Type	**DILH 8 DS10 L280 K GR GFK**
Part No.	**253315**
Conductor support Rd	8 mm
Material of conductor holder	**plastic**
Length (l1)	280 mm
Insulating clearance	220 mm
Permanent temperature range	-30 °C ... +80 °C
Standard	in line with DIN EN IEC 62561-8 (VDE 0185-561-8)

Masterdata	
Net weight	55 g/pc(s)
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364129801
PU	24 pc(s)

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component