
SVK 6.28 FL30 STBL (308 062)







Dimension drawing

Type	SVK 6.28 FL30 STBL
Part No.	**308 062**
Material of clamp	**St/bare**
Clamping range Rd / Fl	6-28 / 30 mm
Screw	⬣ M8 x 45 mm
Material of screw / nut	**St/bare**
Lightning current carrying capability (10/350 µs)	100 kA *)
Standard	EN 62561-1
Short-circuit current (AC 50 Hz / DC) (1 s; ≤ 300 °C)	7.3 kA

Masterdata	
Net weight	156 g/pc(s)
GTIN	4013364344051
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85359000

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

*) For exact assignment, see test certificate.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component