
# Earthing Cables with Cable Lugs open / closed

## EL16 L2.55M 1KSO 8.10 1KSG 10 (416426)





Dimension drawing

| Type | EL16 L2.55M 1KSO 8.10 1KSG 10 |
|---|---|
| **Part No.** | **416426** |
| Cable cross-section | 16 mm² |
| Cable length (l1) | 2.55 m |
| Cable lug open | M8 / M10 |
| Cable lug closed | M10 |
| Bore Ø | 10.5 mm |
| Conductor | **Cu** highly flexible |
| Single wire diameter | 0.1 mm |
| Operating voltage resistance (AC / DC) | 600 V |
| Temperature range | -40 °C ... +150 °C |
| Colour | black ● |
| Material of the cable lug | **Cu/gal Sn** |
| Screw | M4 x 10 mm |
| Screw material | **St/gal Zn** |
| Standard | EN 62561-1 |

| Masterdata | |
|---|---|
| Net weight | 1 pc(s)/st |
| Customs tariff number (Comb. Nomenclature EU) | 85444290 |
| GTIN | 4013364032477 |
| PU | 1 st |

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

Packing in accordance with specifications of the VG standards (defence equipment standards) must be explicitly indicated when ordering.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component