
# Earthing Cables with Cable Lugs open / closed

## EL16 L5.05M 1KSO 8.10 1KSG 8 (416450)






Dimension drawing

| Type | EL16 L5.05M 1KSO 8.10 1KSG 8 |
|---|---|
| **Part No.** | **416450** |
| Cable cross-section | 16 mm² |
| Cable length (l1) | 5.05 m |
| Cable lug open | M8 / M10 |
| Cable lug closed | M8 |
| Bore Ø | 8.5 mm |
| Conductor | **Cu highly flexible** |
| Single wire diameter | 0.1 mm |
| Operating voltage resistance (AC / DC) | 600 V |
| Temperature range | -40 °C ... +150 °C |
| Colour | black ● |
| Material of the cable lug | **Cu/gal Sn** |
| Screw | M4 x 10 mm |
| Screw material | **St/gal Zn** |

| Masterdata | |
|---|---|
| Net weight | 1 pc(s)/st |
| Customs tariff number (Comb. Nomenclature EU) | 85444290 |
| GTIN | 4013364032521 |
| PU | 1 st |

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

Packing in accordance with specifications of the VG standards (defence equipment standards) must be explicitly indicated when ordering.