
Non-sparking, Ex equipotential bonding bar for hazardous areas of zones 1/21, 2/22

PKS 70 10 CUGALNISN (472436)





Dimension drawing

Crimped cable lug according to DIN 46235 with nickel barrier layer to avoid whisker formation.

Type	**PKS 70 10 CUGALNISN**
Part No.	**472436**
Material	**Cu/gal (Ni)Sn**
Lightning impulse current (10/350 µs) Cugal (Ni)Sn 70 mm² (Rm/Rf) / stainless steel 40x10 mm	1HExIIC 100 kA (non-sparking) T4
Max. short-circuit current (AC 50 Hz / DC / 5 s) Cugal (Ni)Sn 70 mm² (Rm/Rf) / StSt 40x10 mm	2600 A / T4
Max. surface temperature T4	135 °C
Cable lug borehole	M10
Conductor cross-section	70 mm²

Masterdata	
Net weight	64.93 g/pc(s)
Customs tariff number (Comb. Nomenclature EU)	85369010
GTIN	4013364470576
PU	3 pc(s)

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

Note: Non-sparking only ensured in connection with PAS EX ...!

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component