DM RD8.10 FL30X3.5 D114MM TPE (478 597)



Water-pressure-tight sealing collar for Round conductors (Ø8–10 mm) and flat conductors (30 x 3.5 mm). With torque control spanner for easy tightening of the two stainless steel tensioning straps. Sealing collar for bushings in case of waterproof foundation slabs / walls (e.g. water-tight concrete construction).

NEW

Type	DM RD8.10 FL30X3.5 D114MM TPE
Part No.	**478 597**
Sealing collar material	**Thermoplastic elastomer (TPE)**
Torque control spanner material	**Polyamide (recycled PA)**
Material of tensioning straps	**StSt**
Diameter of sealing collar	114 mm
Bushing / seal, Rd.	8-10 mm
Bushing / seal, Fl.	30 x 3.5 mm
Pressure-water test	MPA tested to 5 bar
Waterproof concrete construction guideline	Load class 1+2
Resistance	Methane-gas-resistant
Radon	Radon-safe (as per FHRK leaflet MB 101)
Breakaway torque Torque control spanner	3.5 nm

Masterdata	
Net weight	159.88 g/pc(s)
GTIN	4013364523029
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	40169300

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEW: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component