KSB 50 L10M (556 125)



Anti-corrosion tape for protecting underground connections, such as clamp and screw connections.
The permanently plastic anti-corrosion tape, petrolatum-coated on both sides, effectively prevents the penetration of dirt and moisture.

USAGE
- Apply to a clean, dry and grease-free surface
- Wrap the tape in a spiral on the surface to be protected with a 50% overlap
- • Spread and smooth out the insulated surface with your hand
- Optimum usage temperature: 10–30°C

STORAGE
- Store the product in a dry location
- Store the product in its original packaging and protect it from external influences
- Recommended storage temperature: up to 25°C

Type	**KSB 50 L10M**
Part No.	**556 125**
Material	Petrolatum
Colour	brown / beige ●
Length	10 m
Width of tape	50 mm
Tape thickness	≥ 1.1 mm
Max. continuous operating temperature	50 °C

Masterdata	
Net weight	706 g/pc(s)
GTIN	4013364028517
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	68071000

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component