# KSB PERF RED 50 L10M (557 125)



Anti-corrosion tape for protecting underground connections, such as clamp and screw connections.
The permanently plastic anti-corrosion tape, petrolatum-coated on both sides, effectively prevents the penetration of dirt and moisture.

**USAGE**
- Apply to a clean, dry and grease-free surface
- Wrap the tape in a spiral on the surface to be protected with a 50% overlap
- Spread and smooth out the insulated surface with your hand
- Optimum usage temperature: 10–30°C

**STORAGE**
- Store the product in a dry location
- Store the product in its original packaging and protect it from external influences
- Recommended storage temperature: up to 25°C

NEW

| Type | KSB PERF RED 50 L10M |
|---|---|
| **Part No.** | **557 125** |
| Material | Petrolatum |
| Colour | red ● |
| Length | 10 m |
| Width of tape | 50 mm |
| Tape thickness | ≥ 1.1 mm |
| Max. continuous operating temperature | 50 °C |
| Perforation spacing | approx. 200 mm |

| Masterdata | |
|---|---|
| Net weight | 693 g/pc(s) |
| GTIN | 4013364509856 |
| PU | 1 pc(s) |
| Customs tariff number (Comb. Nomenclature EU) | 68071000 |

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEW: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component