EQUITEST (578 321)



For testing the continuity of steel reinforcements in reinforced concrete in accordance with DIN EN 62305-3 as well as the protective and equipotential bonding conductors with a measuring current of 10 A.

The EQUITEST is an accessory for the COMBI G3 installation test device and can only be used in combination with it.

LED indicators for displaying the measurement status.
Recognition of manual and automatic operating modes.

Accessories:• Optical connecting cable to COMBI G3 master device
- Power cable with Schuko Euro plug
- Cable set: 2 cables (L=3,000mm) with integrated alligator clip
- Storage bag
- ISO9000 calibration certificate
- Operating instructions
- Instruction card for operating instructions / software download

NEW

Type	EQUITEST
Part No.	**578 321**
Measurement status display	LED
Test current	>10 A AC
Test function	4 cables
Power supply	230 V / 240 V ±10% – 50 / 60 Hz
Master device interface	Optical / USB interface
Mobile devices interface	Wi-Fi (through HTAnalysis app)
Enclosure material	**Plastic**
Dimension (l x b x t)	210 x 115 x 60 mm

Masterdata	
Net weight	2.4 kg/pc(s)
GTIN	4013364538658
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85444290

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.