Datasheet: HT T2100 earth resistance clamp meter

T2100 (578 322)



Can be used for earth loop measurement and for earthing measurement without an auxiliary earth electrode. Measurement category CAT IV / CAT III.
Automatic calibration, Bluetooth interface, including software.
Can be used as an accessory for the COMBI G3 installation test device.

Wide range of accessories:• Robust protective case
- 4x 1.5-V AA batteries
- Resistance test loop 1 Ω, 5 Ω, 10 Ω
- Operating instructions
- ISO 9000 calibration certificate

NEW

Type	**T2100**
Part No.	**578 322**
Indication	Digital LCD display with backlight
Battery	4x 1.5-V AA batteries
RS-232 interface	4800 baud
Compatible master device	COMBI G3
Resistance measuring range	0.01 to 1,200 Ω
Security	IEC/EN 61010-1; IEC/EN 61010-2-032
Degree of insulation/pollution	Double insulation / 2
Measurement category	CAT IV 400V, CAT III 600V to ground
Loop inductivity resolution	Optical / USB interface
Internal memory	99 measured values
Inside diameter clamp	31 x 48 mm
Enclosure material	**Plastic**

Masterdata	
Net weight	1.93 kg/pc(s)
GTIN	4013364538665
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	90303370

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.