
TE 25 1500 Z STTZN (625 151)





Dimension drawing

Type	TE 25 1500 Z STTZN
Part No.	**625 151**
Material	**St/tZn**
Rod length (l1)	1500 mm
Diameter Ø (d1)	25 mm
Pin diameter	15 mm
Hot-dip galvanisation - single value:	~70 µm
Hot-dip galvanisation - average value:	≥ 55 µm
Tensile strength	410 N/mm²
Static tensile strength (vertical tension)	approx. 32000 N
Specific conductance	≥ 6.66 m / Ohm mm²
Specific resistance	≤ 0.15 Ohm mm² / m
Short-circuit current (AC 50 Hz / DC) (1 s; ≤ 300 °C)	12.3 kA
Standard	EN 62561-2

Masterdata	
Net weight	5.72 kg/pc(s)
GTIN	4013364021853
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85389099

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component