
RE 25 1500 V4A (649 150)





Dimension drawing

Type	RE 25 1500 V4A
Part No.	**649 150**
Material	StSt (V4A)
Material No.	1.4571 / 1.4404 / 1.4401
Rod length	1500 mm
Diameter Ø	25 mm
Standard	EN 62561-2
Wall thickness	2 mm
Cross section	145 mm²
Weight	1.7 kg
Tenon	21 mm
Tensile strength	500-700 N/mm²
Static tensile strength (vertical tension)	approx. 40000 N
Specific conductance	≥ 1.25 m / Ohm mm²
Specific resistance	≤ 0.80 Ohm mm² / m

Masterdata	
Net weight	1.71 kg/pc(s)
GTIN	4013364126350
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85389099

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component