
EAPA 3 KFP 20 B13 (728 522)





Dimension drawing

Type	EAPA 3 KFP 20 B13
Part No.	**728 522**
Fixed point Ø	20 mm
Material of plate	**Aluminium**
Max. cable cross-section Cu	120 mm²
Terminal lug material	4 mm: **Cu/gal Sn**; 6 mm: **HDG steel**
Material (fixed point)	**E-Cu/gal Sn**
Max. short-circuit current I_k 0.5 s	33.5 kA
Max. short-circuit current I_k 1 s	23.7 kA
Standard	EN/IEC 61230 (DIN VDE 0683-100) and fixed points in accordance with DIN 48088-1
Material (threaded pin)	**StSt A2-70**
Hexagon nut	DIN 985-M12-8/gal Zn; DIN 985-M16-8/gal Zn

Masterdata	
Net weight	676 g/pc(s)
GTIN	4013364147874
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85359000

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component