Earthing and Short-Circuiting Devices (partly insulated) for Low-Voltage Cable Distribution Cabinets

EKS TI 2F KVS SBK (745500)

- Partly insulated (TI), shock-proof version
- Fully equipped kit for cable distribution cabinets
- Other cable lengths can be selected online via the earthing and short-circuiting configurator



Kit includes:			
Pos.	Part No.	Pos.	Part No.
2	1x 766 298	7	3x 745 202
4	2x VUKMT58	8	2x 745 602
5	3x 745 302	9	1x 745 400
6	6x 745 018		
For more detailed information on these products, see Accessories chapter.			

Dimension drawing

Type	EKS TI 2F KVS SBK
Part No.	**745500**
Variant No. of EaS device	VUKMT58
Dimensions	440 x 330 x 66 mm
Standard	EN/IEC 61230 (DIN VDE 0683-100)
Temperature range	–25 °C ... +55 °C

Masterdata	
Net weight	7.57 kg/pc(s)
Customs tariff number (Comb. Nomenclature EU)	85369095
GTIN	4013364007888
PU	1 pc(s)

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

Attention: Please state the relevant Variant No. when ordering.