Earthing and Short-Circuiting Devices (fully insulated) for Low-Voltage Cable Distribution Cabinets

EKS VI 2F KVS KK (745903)

- Fully insulated (VI), shock-proof version
- Fully equipped kit for cable distribution cabinets
- Other cable lengths can be selected online via the earthing and short-circuiting configurator



Set – Bestückung:			
Pos.	Art.-Nr.	Pos.	Art.-Nr.
1	1x 745 902	5	6x 745 910
3	2x V162LDM	6	1x 745 922
4	3x 745 905		
Nähere Angaben zu den Artikeln siehe Einzelteile.			

Dimension drawing

Type	**EKS VI 2F KVS KK**
Part No.	**745903**
Variant No. of EaS device	V162LDM
Dimensions	450 x 350 x 110 mm
Standard	EN/IEC 61230 (DIN VDE 0683-100)
Temperature range	–25 °C ... +55 °C

Masterdata	
Net weight	7 kg/pc(s)
Customs tariff number (Comb. Nomenclature EU)	85369095
GTIN	4013364093577
PU	1 pc(s)

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

Note: When ordering, please specify a clear Variant No.