BEV OL PF K (750 211)



Kit includes:		
Type	Part No.	Pos. No.
Tommy bar (**K**) or ratchet (**R**)		
EKV K H 50 12000	1x 751 121	**1**+**4**+**8**+**11**
ESTC SQL RW 5000	1x 769 502	**12**

Dimension drawing

Type	**BEV OL PF K**
Part No.	**750 211**
Type	Tommy bar
Type of cable	Single-pole
Cable cross-section (phase side)	50 mm²
Cable cross-section (earth side)	50 mm²
Length of single-pole cable	12000 mm
Fully insulated	No
Cable length	12000 mm
Standard	EN/IEC 61230 (DIN VDE 0683-100)
Max. short-circuit current I_k 0.06 s	32.0 kA
DB drawing No.	3 Ebgw 01.51
DB Material No.	237 118

Masterdata	
Net weight	15.55 kg/pc(s)
GTIN	4013364123809
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85359000

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

*) Profile-free earthing means that the earthing cable can be suspended on the tower thus allowing for limited diesel locomotive operation.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component