Earthing and Short-Circuiting Devices for Railway Applications

EKV2 50 KKH 600 1800 (751150)



Phase cable end: Two ball head caps (Ø25 mm), hexagon shaft (Part No. 772 320)
Earth cable end: Ball head cap (Ø25 mm), hexagon shaft (Part No. 772 320)

Type	**EKV2 50 KKH 600 1800**
Part No.	**751150**
Material (cable)	Cu
Version	Two-pole
Cable cross-section (phase side)	50 mm²
Cable cross-section (earth side)	50 mm²
Length of phase cable A	600 mm
Length of phase cable C	600 mm
Length of earthing cable	1800 mm
Fully insulated	No
Standard	EN/IEC 61230 (DIN VDE 0683-100) and IEC 61138
Max. short-circuit current I_k 0.06 s	34.0 kA
DB drawing No.	3 Ebgw 01.70
DB Material No.	742 400

Masterdata	
Net weight	1 pc(s)/st
Customs tariff number (Comb. Nomenclature EU)	85359000
GTIN	4013364084520
PU	1 st

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component