PAV 3+1 16 ZAK (758 099)



Type	PAV 3+1 16 ZAK
Part No.	**758 099**
Cable length (A / B / C)	1750 mm
Cable length (D)	3200 mm
Cable cross-section	16 mm²
Cable sheath	transparent
Material (earthing cable)	**Cu, highly flexible**
Clamping range	5-25 mm
Material (contact electrode)	**Cu alloy/gal Sn**
Material (contact and coupling electrode)	**Zamak**
Material (coupling electrode)	**Bronze/gal Sn**
Material (insulating tube)	**Glass-fibre reinforced polyester tube**
Colour (clamp A / B / C)	black
Colour (clamp D)	red
Possible clamp operations	> 500
Max. continuous operating current	10 A
Operating temperature range	-30 °C ... +50 °C
Storage temperature range	-40 °C ... +70 °C
Cable structure	bare fine-stranded Cu wire according to VDE 0295-6
Dielectric strength (cable sheath)	min. 10 kV/mm
Wall thickness (insulation)	1.20 mm (typical)
Insulation	PVC compound TM2 according to HD21.1

Masterdata	
Net weight	3.06 kg/pc(s)
GTIN	4013364287587
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85369095

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.