
PHV1P U 5 36 (759 716)

- Easy transport due to detachable insulating stick





Dimension drawing

Type	**PHV1P U 5 36**
Part No.	**759 716**
Nominal voltage (U_N)	5 ... 10 / 20 ... 36 kV
Type of voltage	a.c.
Total length (l_G)	1730 mm
Insertion depth (I_O)	910 mm
Self-testing element	Yes
Material (test prod)	**Plastic**
Standard	EN/IEC 61481-1 (DIN VDE 0682-431-1)
Material (indicator)	**Plastic, fully insulated**
Temperature range	–25 °C ... +55 °C, climatic category N
Design	Straight
Insulating stick material	**Glass-fibre reinforced polyester tube**
For use at	
For	Indoor and outdoor installations
Type	Single-pole
Indication	Visual
Battery	Lithium AA 1.5 Volt

Masterdata	
Net weight	1.52 kg/pc(s)
GTIN	4013364259270
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	90303370

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component