ES SK STK 2000 (761 003)

- For earthing and short-circuiting devices
- Different lengths
- Light-weight construction
- Hexagon shaft (width A/F 19)
- Plug-in coupling for handle extension





Dimension drawing

Type	ES SK STK 2000
Part No.	**761 003**
Standard	T pin shaft DIN 48087
Total length (l_G)	2000 mm
Temperature range	–25 °C ... +55 °C
Length (handle) (I_H)	1430 mm
Max. load on the operating head	8 kg
For	Indoor and outdoor installations
Material (insulating tube)	**Glass-fibre reinforced polyester tube**
Diameter	30 mm
Supporting head for	Hexagon shaft (width across flats 19 mm)
Anti-rotation plug-in coupling including end fitting	Yes
Type of device	Earthing stick

Masterdata	
Net weight	830 g/pc(s)
GTIN	4013364134348
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	82055980

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component