
EST SK STK 920 (761 070)

- For attaching earthing and short-circuiting devices
- Modular for easy transport
- Light-weight construction
- Hexagon shaft (width across flats 19)
- Plug-in coupling for handle extension





Dimension drawing

Type	EST SK STK 920
Part No.	**761 070**
Standard	T pin shaft DIN 48087
Total length (l_G)	920 mm
Temperature range	–25 °C ... +55 °C
Length (handle) (I_H)	415 mm
Max. load on the operating head	20 kg
For	Indoor and outdoor installations
Material (insulating tube)	**Glass-fibre reinforced polyester tube**
Diameter	30 / 43 mm
Supporting head for	Hexagon shaft (width across flats 19 mm)
Anti-rotation plug-in coupling including end fitting	Yes
Type of device	Earthing stick

Masterdata	
Net weight	800 g/pc(s)
GTIN	4013364136212
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	82055980

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component