
# SCS 36 STK 1000 (763 100)

- For use as operating stick for inserting insulating protective shutters
- Handle termination with plastic plug-in coupling for extending the handle






Dimension drawing

| Type | SCS 36 STK 1000 |
|---|---|
| **Part No.** | **763 100** |
| Nominal voltage ($U_N$) | 1 ... 36 kV |
| Max. load on the operating head | 6 kg |
| Total length ($l_G$) | 1000 mm |
| Insulating clearance ($l_I$) | 525 mm |
| Length (handle) ($I_H$) | 340 mm |
| Insertion depth ($I_O$) | 135 mm |
| Standard (switching stick head) | DIN VDE V 0681-2 |
| Standard (switching stick) | DIN VDE V 0681-1 and -2 |
| Standard (insulating stick) | DIN VDE V 0681-1 |
| For use at | ✷ |
| For | For indoor and outdoor installations |
| Type | Fully insulated, solid switching stick head |
| Material (insulating tube) | **Glass-fibre reinforced polyester tube** |
| Switching pin material | **Steel, plastic-sheathed** |
| Diameter | 30 mm |
| Anti-rotation plug-in coupling including end fitting | Yes |
| Type of device | Switching stick |

| Masterdata | |
|---|---|
| Net weight | 600 g/pc(s) |
| GTIN | 4013364125155 |
| PU | 1 pc(s) |
| Customs tariff number (Comb. Nomenclature EU) | 82055980 |

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component