
SCSN 36 STK 1000 (763 111)

- For use as operating stick for inserting insulating protective shutters
- Handle termination with plastic plug-in coupling for extending the handle





Dimension drawing

Type	SCSN 36 STK 1000
Part No.	**763 111**
Nominal voltage (U_N)	1 ... 36 kV
Max. load on the operating head	6 kg
Total length (l_G)	1000 mm
Insulating clearance (l_I)	525 mm
Length (handle) (I_H)	340 mm
Insertion depth (I_O)	135 mm
Standard (switching stick head)	DIN VDE V 0681-2
Standard (switching stick)	DIN VDE V 0681-1 and -2
Standard (insulating stick)	DIN VDE V 0681-1
For use at	
For	Indoor and outdoor installations
Type	Fully insulated, solid switching stick head
Material (insulating tube)	**Glass-fibre reinforced polyester tube**
Switching pin material	**Steel, sheathed overall in plastic**
Diameter	30 mm
Anti-rotation plug-in coupling including end fitting	Yes
Type of device	Switching stick

Masterdata	
Net weight	580 g/pc(s)
GTIN	4013364137226
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	82055980

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component