
SCS 36 1500 (763 611)

- For use as operating stick for inserting insulating protective shutters
- Handle termination with end cap





Dimension drawing

Type	SCS 36 1500
Part No.	**763 611**
Nominal voltage (U_N)	1 ... 36 kV
Max. load on the operating head	7.5 kg
Total length (l_G)	1500 mm
Insulating clearance (l_I)	525 mm
Length (handle) (I_H)	560 mm
Insertion depth (I_O)	415 mm
Standard (switching stick head)	DIN VDE V 0681-2
Standard (switching stick)	DIN VDE V 0681-1 and -2
Standard (insulating stick)	DIN VDE V 0681-1
For use at	✷
For	For indoor and outdoor installations
Type	Fully insulated, solid switching stick head
Material (insulating tube)	**Glass-fibre reinforced polyester tube**
Switching pin material	**Steel, plastic-sheathed**
Diameter	30 mm
Anti-rotation plug-in coupling including end fitting	No
Type of device	Switching stick

Masterdata	
Net weight	610 g/pc(s)
GTIN	4013364076921
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	82055980

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.