
SZ HH 1500 (765 042)

- 20° angled operating head for HH fuses that are not easily accessible





Dimension drawing

Type	SZ HH 1500
Part No.	**765 042**
Nominal voltage (U_N)	1 ... 36 kV
Standard	DIN VDE V 0681-3
Clamping range	30 ... 50*) / 50 ... 90 mm
Total length (l_G)	1500 mm
Type	Straight clamping head
Insulating clearance (l_I)	525 mm
Insulating stick material	**Glass-fibre reinforced polyester tube**
Length (handle) (I_H)	790 mm
Insertion depth (I_O)	185 mm
For use at	✷
For	Indoor and outdoor installations
Material (operating head)	**Glass-fibre reinforced polyamide**
Material (reducing insert)	**Polyamide**
Material (adjustable handle)	**Polyamide**
Diameter	43 mm
Colour	Grey
Anti-rotation plug-in coupling including end fitting	No
Type of device	Fuse tong

Masterdata	
Net weight	2.59 kg/pc(s)
GTIN	4013364093775
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	82055980

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

*) Only if used with reducing insert