
Datasheet: SZ Fuse Tongs

SZ HH W20 1250 (765 051)

- 20° angled operating head for HH fuses that are not easily accessible





Dimension drawing

Type	SZ HH W20 1250
Part No.	**765 051**
Nominal voltage (U_N)	1 ... 36 kV
Standard	DIN VDE V 0681-3
Clamping range	30 ... 50*) / 50 ... 90 mm
Total length (l_G)	1250 mm
Type	20° angled clamping head
Insulating clearance (l_I)	525 mm
Insulating stick material	**Glass-fibre reinforced polyester tube**
Length (handle) (I_H)	530 mm
Insertion depth (I_O)	195 mm
For use at	✷
For	Indoor and outdoor installations
Material (operating head)	**Glass-fibre reinforced polyamide**
Material (reducing insert)	**Polyamide**
Material (adjustable handle)	**Polyamide**
Diameter	43 mm
Colour	Grey
Anti-rotation plug-in coupling including end fitting	No
Type of device	Fuse tong

Masterdata	
Net weight	2.29 kg/pc(s)
GTIN	4013364093799
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	82055980

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

*) Only if used with reducing insert

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component