
IS 36 SK 1500 (766 002)

- For use as switching, operating and earthing stick
- Handle closed with end cap





Dimension drawing

Type	IS 36 SK 1500
Part No.	**766 002**
Nominal voltage (U_N)	1 ... 36 kV
Total length (l_G)	1500 mm
Insulating clearance (l_I)	525 mm
Length (handle) (I_H)	500 mm
Insertion depth (I_O)	475 mm
Standard (insulating stick)	DIN VDE V 0681-1
For	Indoor and outdoor installations
Material	**Glass-fibre reinforced polyester tube**
Diameter	30 mm
For use at	✷
Supporting head for	Hexagon shaft
Anti-rotation plug-in coupling including end fitting	No
Type of device	Insulating stick

Masterdata	
Net weight	810 g/pc(s)
GTIN	4013364017832
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	82055980

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component