
IS 36 SQ STK 1000 (766 301)

- For use as switching, operating and earthing stick
- Handle closed with plastic plug-in coupling for extending the handle





Dimension drawing

Type	IS 36 SQ STK 1000
Part No.	**766 301**
Nominal voltage (U_N)	1 ... 36 kV
Total length (l_G)	1025 mm
Insulating clearance (l_I)	525 mm
Length (handle) (I_H)	350 mm
Insertion depth (I_O)	150 mm
Standard (insulating stick)	DIN VDE V 0681-1
For	Indoor and outdoor installations
Material	**Glass-fibre reinforced polyester tube**
Diameter	30 mm
For use at	✷
Supporting head for	T pin shaft
Anti-rotation plug-in coupling including end fitting	Yes
Type of device	Insulating stick

Masterdata	
Net weight	400 g/pc(s)
GTIN	4013364125124
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	82055980

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component