
# IS 72.5 SQ SN7743 (766 312)

- For use as switching, operating and earthing stick
- Handle closed with end cap






Dimension drawing

| Type | IS 72.5 SQ SN7743 |
|---|---|
| **Part No.** | **766 312** |
| Nominal voltage ($U_N$) | 1 ... 72.5 kV |
| Total length ($l_G$) | 1300 mm |
| Insulating clearance ($l_I$) | 900 mm |
| Length (handle) ($I_H$) | 310 mm |
| Insertion depth ($I_O$) | 90 mm |
| Standard (insulating stick) | E DIN VDE V 0681-1 |
| For | Indoor and outdoor installations |
| Material | **Glass-fibre reinforced polyester tube** |
| Diameter | 30 mm |
| For use at | ✷ |
| Supporting head for | T pin shaft |
| Anti-rotation plug-in coupling including end fitting | No |
| Type of device | Insulating stick |

| Masterdata | |
|---|---|
| Net weight | 540 g/pc(s) |
| GTIN | 4013364311985 |
| PU | 1 pc(s) |
| Customs tariff number (Comb. Nomenclature EU) | 82055980 |

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

*) Max. weight of insulating shutters, for example.