PHE 15 16.7 4T TA (766 616)

- For use in wet weather conditions
- For overhead contact lines of electrical railways
- With self-testing element
- Visual indication
- Easy transport due to detachable insulating sticks
- Consisting of four elements
- Storage bag included in delivery



Dimension drawing

For overhead contact lines of electric railways

Type	**PHE 15 16.7 4T TA**
Part No.	**766 616**
Nominal voltage (U_N)	15 kV
Standard	DIN VDE 0681-6
Frequency	16.7 Hz
Indication	Visual
Self-testing element	Yes
Total length (l_6)	4890 mm
Insulating clearance (l_1)	685 mm
Material (test electrode)	**St/gal Zn**
Insertion depth (I_0)	1675 mm
Material (test prod)	**Glass-fibre reinforced polyester tube**
Length (test prod)	1900 mm
Material (indicator)	**Plastic, fully insulated**
Insulating stick material	**Glass-fibre reinforced polyester tube**
Length of the operating stick (with hand guard)	640 mm
Length of the operating stick (end fitting)	2530 mm
DB drawing No.	3 Ebgw 02.51
DB Material No.	237 129
Design	Complete
For use at	
For	Outdoor installations
Application	Overhead contact lines of electric railways
Type	Single-pole
Battery	Lithium

Masterdata	
Net weight	5.09 kg/pc(s)
GTIN	4013364126091
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	90303370

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component