Two-pole SPN voltage detector for power supply

SPN 500B (766660)



Type	SPN 500B
Part No.	**766660**
Nominal voltage range (U_N)	50 ... 500 V
Frequency range	15 ... 500 Hz and DC
Dimensions (indicator)	274 x 75 x 47 mm
Standard	EN/IEC 61243-3 (DIN VDE 0682-401)
Temperature range	–15 °C ... +45 °C
Material (indicator)	**Safety enclosure made of solid rubber**
Indication	Direct-reading instrument, LCD and LED
Connecting cable	PUR-sheathed cable, highly flexible, 1000 mm
Overvoltage category	CAT IV 500 V
Type	Two-pole
Battery	Lithium
For	Indoor and outdoor installations
Degree of protection	IP 65
For use at	

Masterdata	
Net weight	1 pc(s)/st
Customs tariff number (Comb. Nomenclature EU)	90303370
GTIN	4013364302464
PU	1 st

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component