
Datasheet: PHG II Voltage Detector

PHG2 20 (766 720)





Dimension drawing

Category „“S““ for indoor switching stations

Type	PHG2 20
Part No.	**766 720**
Nominal voltage (U_N)	20 kV
Type of voltage	a.c.
Total length (l_c)	1425 mm
Insertion depth (I_O)	720 mm
Standard	EN/IEC 61243-1 (DIN VDE 0682-411)
Temperature range	–25 °C ... +55 °C, climatic category N
Design	Complete
For use at	✷
For	Indoor installations
Application	Switchgear installations
Type	Single-pole
Indication	Visual, three LEDs
Function	Passive voltage detector without batteries
Material (test electrode)	**Cu/gal Sn**
Material (test prod)	**Glass-fibre reinforced polyester tube**
Material (indicator)	**Plastic**
Insulating stick material	**Glass-fibre reinforced polyester tube**

Masterdata	
Net weight	1.7 kg/pc(s)
GTIN	4013364094321
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	90303370

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component