
PHE3 25 S 50 1P (767 125)

- Easy transport due to detachable insulating stick (M12) and test prod
- Insulating stick with plug-in coupling for extending the handle





Dimension drawing

For overhead contact lines of electric railways
Category „“S““ for single-ended monophase systems

Type	**PHE3 25 S 50 1P**
Part No.	**767 125**
Nominal voltage (U_N)	25 kV
Type of voltage	a.c.
Category	S 64
Total length (l_G)	1680 mm
Insertion depth (I_O)	880 mm
Standard	EN/IEC 61243-1 (DIN VDE 0682-411)
Temperature range	-25 °C ... +55 °C, climatic category N
Design	Complete
For use at	
For	Outdoor installations
Application	Overhead contact lines of electric vehicles
Type	Single-pole
Indication	Acoustic and visual
Self-testing element	Yes
Material (test electrode)	**Copper alloy/gal Sn**
Material (test prod)	**Glass-fibre reinforced epoxy resin tube**
Material (indicator)	**Plastic, fully insulated**
Insulating stick material	**Glass-fibre reinforced polyester tube**

Masterdata	
Net weight	1.26 kg/pc(s)
GTIN	4013364130319
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	90303370

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.