
PHE3S 110 132 S (767 131)

- Easy transport due to detachable test prod and modular insulating stick





Kit includes:		
Type	Part No.	Pos. No.
PHE3 110 132 S	767 130	**1**+**8**+**21**+**22**+**32**+**33**+**36**
KLT 133 34 10	766 996	**38**

Dimension drawing

For 50 Hz three-phase systems and 16.7 Hz centre-earthed monophase traction power lines
Range does not have to be switched

Type	**PHE3S 110 132 S**
Part No.	**767 131**
Nominal voltage (U_N)	110 ... 132 kV
Type of voltage	a.c.
Frequency	50 and 16.7 Hz
Category	S
Total length (I_G)	3440 mm
Insertion depth (I_0)	880 mm
Standard	EN/IEC 61243-1 (DIN VDE 0682-411)
Temperature range	–25 °C ... +55 °C, climatic category N
Design	Complete
For use at	
For	For indoor and outdoor installations
Application	Switchgear installations and overhead lines
Type	Single-pole
Indication	Acoustic and visual
Self-testing element	Yes
Material (test electrode)	**Copper alloy/gal Sn**
Material (test prod)	**Glass-fibre reinforced epoxy resin tube**
Material (indicator)	**Plastic, fully insulated**
Insulating stick material	**Glass-fibre reinforced polyester tube**
DB drawing No.	3 Eku 710 001
DB Material No.	01 101 358

Masterdata	
Net weight	6.2 kg/pc(s)
GTIN	4013364139411
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	90303370

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component