PS DCA HR LRM (767 150)



Kit in a plastic case for verifying safe isolation from supply voltage, the interface and in-phase conditions in HR and LRM systems.

Type	**PS DCA HR LRM**
Part No.	**767 150**
Nominal voltage (U_N)	1 ... 45 kV
Frequency	50 Hz
Dimensions	395 x 295 x 105 mm
Self-testing element	Yes
Standard	EN/IEC 61243-5 (DIN VDE 0682-415)
Temperature range	–25 °C ... +55 °C
Application	Verifying safe isolation from supply voltage and in-phase conditions
Indication	Visual
Type of system	HR and LRM

Masterdata	
Net weight	1.94 kg/pc(s)
GTIN	4013364139473
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	90303370

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component